



irrifrance

SUPER MINI Bellows



SUPER MINI BELLOWS

Ø 63 - 280 m
Ø 70 - 200 m

Hydraulic performances

Model	Ø PE	PE Length (m)	PE Thickness (mm)	Flow Rate (m ³ /h)	Inflow Pressure (Bars)	Irrigated strip width (m)	Average Area (ha)
Super	ø 63	280	4,7	8 - 24	5 - 10	42 - 60	1,5
Mini	ø 70	200	5	8 - 30	5 - 10	54 - 72	1,3

Technical characteristics

Model	Height (m)	Width (m)	Length ex trolley (m)	Length in trolley (m)	Height under frame	Tyres	Weight ex water	Weight inc water
Super Mini	2,05	1,75	2,90	4,75	0,28	185 x 70 x 13	700	1000

SUPER MINI bellow



Bellows 8" drive



Hydrofilter engine



Manual winch trolley lifting



Speed regulation



Automatic trolley hooking



Mechanical jack and rotation of the turntable

Motorization :

- Bellows drive with mechanical speed regulation

Standard equipment

- Automatic trolley hooking
- Rotation of the turntable
- Galvanised trolley with adjustable track
- Winch trolley lifting

Options

- Discharge valve
- Shut-off valve
- Mechanical rotation of the turntable
- Adjustable front jack
- skid or wheel kit
- Low trolley (for flow above 25 m³/h)

irrifrance

Irrigation Systems 34230 Paulhan - France

E-mail : irrifrance@irrifrance.com - Web : www.irrifrance.com

Tél.: 04 67 25 79 79 - Fax : 04 67 25 10 35 - Tél. inter.: + 33 4 67 40 79 20 - Fax inter.: + 33 4 67 40 79 21